



MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET

Trident



AUTOMOTIVE



DATA SHEET NO: 5995

PRODUCT NAME/VISCOSITIES:

TRIDENT 5w30

DESCRIPTION:

A semi synthetic high performance engine oil formulated to meet the demanding requirements of today's engines.

APPLICATION:

Recommended for use in modern vehicles where this type of oil is specified by the manufacturer. Trident 5w30 is especially recommended for use in many modern petrol and diesel vehicles that require a fuel efficient lubricant.

USER BENEFITS:

- Provides easy starting and quick circulation of the oil even under very cold conditions
- Helps to maximise fuel economy and minimise emissions
- Protects against wear under arduous operating conditions and allows the use of the modern longer oil change service intervals

PERFORMANCE PROFILE:

- ACEA A3 / B3, A3 / B4
- API SL, CF
- Meets the requirements of MB 229.1
- Suitable for engines requiring a 5w30 grade oil including Ford and many Japanese models.

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade		5w30
Specific Gravity @ 15°C	0.855	
Kinematic Viscosity @ 100°C		11.2cSt
Kinematic Viscosity @ 40°C	63.9cSt	
Viscosity Index	170	
Pour point °C		<-42
Flashpoint °C		>200
Cold Crank Viscosity @ -30°C		6,600cP max

HEALTH AND SAFETY:

Health and Safety Data Sheet 5995 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

