



CLASSIC PLUS 15W-50

Premium Mineral Engine Oil

Issue: July 2019

PRODUCT CODE	PACK SIZE	CTN / QTY
CLASP005	5 Litre	4



Description

CLASSIC PLUS is a premium mineral, multigrade engine oil made from pure hydrocracked base oil in combination with superior engine protection and anti-rust additive technology.

CLASSIC PLUS meets API SL/CF-4 engine oil specifications as well as the obsolete European CCMC G1/G2/D4 and PD1 specifications.

It is a SAE 15W-50 and contains optimised **ZINC** levels for added anti-wear protection in older engines

Applications

CLASSIC PLUS is suitable for passenger cars, motorcycles, 4WD's, and commercial vehicles that originally specified SAE 20, SAE 15W-40 or SAE 15W-50.

The superior low temperature flow of **CLASSIC PLUS** compared to SAE 20W-50 oils will allow the engine to reach the required oil pressure more rapidly and provide faster engine warm up times, protecting the engine faster than 20W-50 oils in winter or cooler months.

CLASSIC PLUS is also our first choice for Classic medium- and heavy-duty diesel engines where lower detergency is required and that originally used SAE 15W-40, SAE 30 or SAE 20W-40 oils. If higher detergency is required, we recommend Penrite HPR Diesel 15 SAE 15W-50. If excessive oil consumption is being experienced, we recommend Penrite HPR Diesel SAE 20W-60. Please check your operator manual to ensure the appropriate API or CCMC specifications are met.

Product Benefits

- Contains a balanced formulation of modern additives to suit vehicles of this period, exceeding the originally required oil specifications
- Contains an advanced anti-rust additive to protect engines in mid- to long-term storage,
- Maintains engine cleanliness and includes optimised zinc levels for wear protection
- Shear stable formulation
- Suitable for use as a winter and summer engine oil
- Faster oil flow at start up than 20W-50, especially in colder conditions.
- Better operating temperature protection than SAE 15W-40 oils.

Industry Specifications

API SL/CF-4 ACEA A2/B2 (obsolete) CCMC G1/G2/D4/PD1 (obsolete) MIL-L-46152 (obsolete)

Typical Data

Density at 15°C, kg/L	0.869
Flash Point, °C	210
Viscosity, Kinematic, cSt	
at 40°C	142
at 100°C	18.7
Viscosity Index	149
Viscosity, Cold Cranking @ -20 °C	6185
Magnesium, mass %	0.136
Zinc, mass %	0.125
Phosphorus, mass %	0.098
Base Number	7.6

Information in this sheet is based on recent production. Minor variations to typical properties are expected in normal manufacture and do not affect product performance. An MSDS is available on request.



PENRITE OIL COMPANY PTY LTD

110-116 Greens Road Dandenong South 3175 Victoria AUSTRALIA

ABN 25 005 001 525

Phone 1300-PENRITE (1300 736 748)

International: Phone: 61 3 9801 0877

New Zealand Phone: 0800 533 698

Website: www.penriteoil.com

Fax: 1800-PENRITE (1800 736 748)

Fax: 61 3 9801 0977

Fax: 0508 736 748

Email: penrite@penriteoil.com

**PROUDLY AUSTRALIAN
FAMILY OWNED
SINCE 1926**



PENRITE