

Product Code: 5991 Sector: Automotive

Issue No: 1

Issue Date: 23/07/20

## TRIDENT PROFESSIONAL ENGINE OIL 10w40

Semi synthetic, full SAPS, for use in petrol and diesel engines.

### Application

A professional engine oil suitable for the latest engine technology. Designed to meet OEM specifications. Recommended for engines requiring a 10w40 viscosity meeting the below manufacturer specifications and MTF-94 Gear Oil Specification.

### Performance Profile

ACEA A3/B4, ACEA A3/B3  
API SN, SM, SL, CF

### Suitable for

BMW Longlife-98  
Fiat 9.55535-G2, Fiat 9.55535-D2  
MB 229.3, MB 229.1  
PSA B71-2300 <2014, PSA B71-2295  
PSA B71-2294  
Renault RN0700 / RN0710  
VW 502 00 / 505 00, VW 500 00 / 501 01  
Land Rover MTF-94 Gear Oil Specification

### Features & Benefits

- Excellent low temperature flow when cold starting, helping to instantly protect vital components.
- Viscosity stability at high temperatures, delivering reduced wear and tear on the engine and its components.
- Formulated with technology to provide engine cleanliness and durability which reduces emissions and provides extended drain capability.
- Millers Oils stop start technology delivers instant protection under hot or cold conditions.

### Typical Characteristics

Density @ 15°C, g/ml	0.870
Kinematic Viscosity @ 100°C, cSt.	14.0
Flashpoint, °C	>200

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website

[www.millersoils.co.uk](http://www.millersoils.co.uk)

**Footnotes:** SAPS – Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer



MADE IN BRITAIN 

Millers Oils Ltd  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)